

# EXAMGOOD

## QUESTION & ANSWER

Exam Good provides update free of charge in one year!

Accurate study guides  
High passing rate!

<http://www.examgood.com>

**Exam : 300-425**

**Title : Designing Cisco Enterprise  
Wireless Networks  
(ENWLSD)**

**Version : DEMO**

## 1.DRAG DROP

Drag and drop the characteristics from the left onto the correct functionalities on the right.

complex configuration on the Cisco WLC and infrastructure	Multiple AP-Manager Interfaces
achieves optimal AP join process with src-dst-ip load-balancing	
simple configuration on the Cisco WLC and infrastructure	LAG
avoids single point of failure on neighbor switches	

**Answer:**

complex configuration on the Cisco WLC and infrastructure	Multiple AP-Manager Interfaces
achieves optimal AP join process with src-dst-ip load-balancing	avoids single point of failure on neighbor switches
simple configuration on the Cisco WLC and infrastructure	complex configuration on the Cisco WLC and infrastructure
avoids single point of failure on neighbor switches	LAG
	simple configuration on the Cisco WLC and infrastructure
	achieves optimal AP join process with src-dst-ip load-balancing

**Explanation:**

[https://www.cisco.com/c/en/us/td/docs/wireless/controller/7-](https://www.cisco.com/c/en/us/td/docs/wireless/controller/7-4/configuration/guides/consolidated/b_cg74_CONSOLIDATED/b_cg74_CONSOLIDATED_chapter_010100001.html)

[4/configuration/guides/consolidated/b\\_cg74\\_CONSOLIDATED/b\\_cg74\\_CONSOLIDATED\\_chapter\\_010100001.html](https://www.cisco.com/c/en/us/td/docs/wireless/controller/7-4/configuration/guides/consolidated/b_cg74_CONSOLIDATED/b_cg74_CONSOLIDATED_chapter_010100001.html)

2.Which UDP port numbers are used for exchange mobility packets in an AireOS wireless deployment?

- A. UDP 16666 for control plane, EoIP (IP protocol 97) for data plane
- B. UDP 16668 for control plane, UDP 16667 for data plane
- C. UDP 16667 for control plane, UDP 16666 for data plane

D. UDP 16666 for control plane, UDP 16667 for data plane

**Answer: A**

**Explanation:**

• Enable these UDP ports for Mobility traffic:

- 16666 – Secured Mode
- 16667 – Unsecured Mode

3.A customer asks an engineer to explain the concept of mobility domains and mobility groups.

Which statement does the engineer respond with?

- A. A mobility group does not constrain the distribution of security context of a client and also does not constrain AP fail-over between controllers when the WLC are in the same mobility domain.
- B. If WLCs are in the same mobility domain, they communicate with each other but, if an anchor WLC is present it must be in the same mobility domain for communication to be possible.
- C. If WLCs are in the same mobility domain, they communicate with each other. Mobility groups constrain the distribution of security context of a client and also constrain AP fail-over between controllers.
- D. WLCs do not need to be in the same mobility domain to communicate with each other. Mobility groups constrain the distribution of security context of a client and also constrain AP fail-over between controllers.

**Answer: C**

**Explanation:**

[https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-0/configuration-guide/b\\_cg80/b\\_cg80\\_chapter\\_010011.html](https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-0/configuration-guide/b_cg80/b_cg80_chapter_010011.html)

4.An engineer is designing a wireless deployment for a university auditorium.

Which two features can be used to help deal with the issues introduced by high AP count? (Choose two.)

- A. TSPEC
- B. RXSOP
- C. TPC
- D. LSS
- E. DFS

**Answer: C,E**

**Explanation:**

<https://www.cisco.com/c/en/us/support/docs/wireless-mobility/80211/200069-Overview-on-802-11h-Transmit-Power-Cont.html>

5.A wireless engineer is designing a wireless network to support real-time applications over wireless.

Which IEEE protocol must the engineer enables on the WLC so that the number of packets that are exchanged between an access point and client are reduced and fast roaming occurs?

- A. 802.11w
- B. 802.11r
- C. 802.11i

D. 802.11k

**Answer: D**

**Explanation:**

802.11r reduces the number of packets that are exchanged between the client and an AP. The client preauthenticates to the AP it will roam to before actually roaming. This means the roam itself occurs faster because the AP already has the client authentication credentials cached, resulting in fewer packets required between the client and the AP.