

QUESTION & ANSWER

Exam Good provides update free of charge in one year!



Exam : 920-249

Title : Nortel Application Switch

Ris.23XConfig &Admin

Version: DEMO

1. Which three commands would be useful when troubleshooting an issue with WCR? (Choose three.)
A. /cfg/slb/cur
B. /stats/slb/cur
C. /info/slb/dump
D. /info/l3/vrrp/dump
E. /info/slb/sess/dump Answer:ACE
2. Each switch filter can be set to only one of four possible choices: allow, deny, and redirect are three of them. Which is the fourth choice?
A. cloak traffic
B. stack traffic
C. disable traffic
D. translate traffic Answer: D
3. What happens to a WCR filter when all real servers in the associated group fail?
A. The filter becomes a deny filter.
B. The filter becomes an allow filter.
C. The filter is ignored and traffic will be dealt with by the next matching filter.
D. The backup action specified in the advanced filter menu will be used instead of redirection. Answer: B
4. What does Virtual Matrix Architecture (VMA) do?
A. VMA allows filtering to be configured on all physical ports.
B. VMA allows the switch to process TCP traffic from telnet sessions.
C. VMA takes individual resources from any back-up switch and utilizes them for load balancing.

D. VMA makes use of any unused resources within a switch by distributing the workload to multiple processors. Answer: D
Allswell. D
5. Which two requirements are necessary for an application switch? (Choose two.)
A. edge routing
B. no clustering
C. session-based traffic management
D. single point of control for traffic to web components Answer: CD
6. Which is the minimum platform requirement for a system with 14 simultaneous fast Ethernet connections and a single fiber connection?
A. 2208
B. 2216
C. 2424SSL
D. 3408 Answer: B
7. Which two are valid characteristics of content identifiers, such as URLs. (Choose two.)
A. They can be of varying lengths.
B. They have to be of constant lengths.
C. They can be terminated by VLAN tagging.
D. They can appear at unpredictable locations within a request. Answer:AD
8. Why is delayed binding necessary when doing URL or content-based switching?
A. Layer 7 information is not sent in the first packet.
B. It prevents DOS attacks against web services.

C. It creates the correct source IP for traffic returning from the realserver.

Answer:A
9. By default, how are non-GET requests handled in URL based WCR?
A. dropped
B. sent to a cache
C. forwarded to the origin server
D. load balanced across the cache server group
Answer: C
10. For Layer 7 load balancing, where must the sub-string match "/profit" be located in the URL?
A. inside the first 32 bits
B. inside the first 64 bytes
C. immediately following the FQDN
D. slash not specified in a sub-string match Answer: C