EXAMGOOD

QUESTION & ANSWER

Exam Good provides update free of charge in one year!

Accurate study guides

High passing rate!

http://www.examgood.com

Exam: C4040-221

Title : AIX 7 Administration

Version: DEMO

1.The following information has been reported in an AIX error log:

```
LABEL:        DMPCHK_NOSPACE
    IDENTIFIER:    F89FB899
    Date/Time:      Mon 22 Aug 15:00:01 2011
    Sequence Number: 6
    Machine Id:     00E65BECF00
    Node Id:        lpar1
    Class:          O
    Type:           PEND
    WPAR:           Global
    Resource Name:   dumpcheck
    Description
    The copy directory is too small.
    Probable Causes
    There is not enough free space in the file system containing the copy directory to
    accommodate the dump.
      Recommended Actions
      Increase the size of that file system.
      Detail Data
      File system name
      /var/adm/ras
      Current free space in kb      119740
      Current estimated dump size in kb      271564
```

How can the administrator prevent the error from reoccurring?

A. Create a secondary dump device greater than 266MB

B. Increase primary dump device size greater than 266MB

C. Increase “/var" file system to ensure it has a minimum of 266MB free space

D. Increase "/var/adm/ras/livedump" file system to ensure it has a minimum of 266MB free space

Answer:C

2.What is the difference between deferred and concurrent firmware updates.?

A. Deferred firmware can be applied concurrently but contains updates that affect the internal program load path, which are not activated until the next time the server is shut down and restarted.

B. Concurrent firmware must be done on all LPARs in the frame at the same time. Deferred firmware can be loaded on each LPAR at a different time and only becomes active when the LPAR is shutdown and restarted.

C. Deferred firmware can only be applied during an outage to the managed system as it will automatically shut the managed system down during its installation.

D. Concurrent firmware is only for minor fixes to the system mircocode while deferred firmware contains major fixes to the service processor.

Answer:A

3.A host has a single virtual Ethernet adapter (ent0) configured with only a default PVID, and the administrator is trying to determine why it cannot be used to reach any other system on the network. He suspects that it may be caused by a problem in the VLAN configuration.

How would the administrator determine the VLAN for which the adapter was configured?

A. Use the command 'lsdev -l ent0' on the host to determine the port VLAN ID.
B. Use the command 'lsattr-El ent0' on the host to determine the port VLAN ID.
C. Look on the HMC to determine which VLAN is configured for the adapter.
D. Examine the Shared Ethernet Adapter on the Virtual I/O Server to determine which VLAN the adapter is using.
Answer:C

4.How can an administrator disable Role Based Access Control (RBAC) in a WPAR?
A. Run chattr -E -l sys0 -a enhanced_RBAC=false Reboot the WPAR
B. Run the RBAC wizard and deselect 'Enable RBAC Reboot the system
C. Run chdev -l mywpar -a enhanced_RBAC=false Reboot the Global Environment
D. Run chwpar -a RBAC=false Reboot the WPAR
Answer:C

5.After performing a NIM rte install, the administrator noticed that not all filesets are at the correct Technology Level (TL).
What action will help the administrator determine why the inconsistent fileset levels were installed?
A. On the NIM server, run an lppchk to identify if the Software Vital Product Data is valid.
B. On the NIM client, run oslevel command against the TL to identify missing prerequisites.
C. Run instfix command on NIM client to determine what filesets are inconsistent.
D. On the NIM server run the NIM lslpp command to indentify downlevel filesets contained in the lpp_source.
Answer:D