

QUESTION & ANSWER

Exam Good provides update free of charge in one year!



Exam: HPE0-S58

Title : Implementing HPE

Composable Infrastructure

Solutions Exam

Version: DEMO

1. During an initial setup of a Synergy environment, an integrator needs to enable or disable authorized Service access.

What will be the outcome when the integrator disables this service?

- A. Authenticated administrators will be unable to make changes to the system
- B. Authorized users will be unable to generate a support dump
- C. Authenticated administrators will be unable to access the system
- D. Authorized support will be unable to diagnose the system

Answer: D Explanation:

Reference: https://support.hpe.com/hpsc/doc/public/display?docId=emr_na-c05098314 (62)

2.FILL BLANK

A customer has the following configuration:

Frame 1

- Bay 1 HPE Synergy 12Gb SAS Connection Module
- Bay 2
- Bay 3 HPE Virtual Connect SE 40 GB F8 Module
- Bay 4 HPE Synergy 12GB SAS Connection Module
- Bay 5
- Bay 6 HPE Synergy 10 Gb Interconnect Link Module

Frame 2

- Bay 1 HPE Synergy 12Gb SAS Connection Module
- Bay 2
- Bay 3 HPE Synergy 10Gb Interconnect Link Module
- Bay 4 HPE Synergy 12Gb SAS Connection Module
- Bay 5
- Bay 6 HPE Virtual Connect SE 40Gb F8 Module

How many more frames can the customer add to their Synergy composable fabric? (Note: Enter your answer in the answer field below.)

Answer:

Explanation:

Frame 1 – Bay 2 – HPE Virtual Connect SE 100Gb F32 Module for Synergy (867796-B21)

Frame 1 – Bay 5 – HPE Virtual Connect SE 16Gb Fibre Channel Module for Synergy (779227-B21)

Frame 2 – Bay 2 – Brocade 16Gb/24 Power Pack+ Fibre Channel SAN Switch Module for HPE Synergy (K2Q86A)

Frame 2 – Bay 5 – HPE Synergy 4820C 10/20/25Gb Converged Network Adapter (876449-B21)

3.In a 3-frame HPE Synergy environment, how should an integrator place the image Streamer modules to allow for redundancy to all of the management connections?

A. one Image Streamer module in frame 2, and a second Image Streamer Module in frame 3 (2 total)

- B. two Image Streamer modules in frame 2, and two Image Streamer modules in frame 3 (4 total)
- C. one Image Streamer module in each Synergy frame (3 total)
- D. two Image Streamer modules in frame 1 (2 total)

Answer: B

Explanation:

Reference: https://www.karma-group.ru/upload/iblock/2be/synergy_image_streamer.pdf (page 7)

- 4. What must an integrator do before an existing cluster can be imported to the HPE Composer?
- A. The vCenter Server must be integrated with the HPE Composer
- B. The cluster must be vSAN enabled
- C. The HPE Composer must have at least two management interfaces to connect to the cluster
- D. The cluster must be enabled for HPE Composer integration

Answer: A

5.Refer to the exhibit.

Interconnect Bay



Rear of HPE Synergy Frame

How should an integrator pair interconnect bays to set up redundant fabrics in an HPE Synergy 12000 Frame?

- A. Interconnect bays 1 and 2; bays 3 and 4; bays 5 and 6.
- B. Interconnect bays 1 and 6; bays 2 and 5; bays 3 and 4.
- C. Interconnect bays 1 and 4; bays 2 and 5; bays 3 and 6.
- D. Interconnect bays 1 and 3; bays 2 and 4; bays 5 and 6.

Answer: C **Explanation:**

