

QUESTION & ANSWER

Exam Good provides update free of charge in one year!



Exam : JN0-348

Title : Enterprise Routing and

Switching, Specialist

Version: DEMO

- 1. What are two benefits of 802.3ad link aggregation? (Choose two.)
- A. It increases bandwidth.
- B. It ensures symmetrical paths.
- C. It simplifies interface configuration.
- D. It creates physical layer redundancy.

Answer: AD

- 2. Which statement is true about IP-IP tunnels?
- A. Intermediate devices must have a route to the destination address of the traffic being tunneled.
- B. Intermediate devices must have a route to both the tunnel source address and the tunnel destination address.
- C. Intermediate devices must have a route to the tunnel destination address but do not require a route to the tunnel source address.
- D. Intermediate devices must have a route to the tunnel source address but do not require a route to the tunnel destination address.

Answer: C

3. You have a conference room with an open network port that is used by employees to connect to the network. You are concerned about rogue switches being connected to this port.

Which two features should you enable on your switch to limit access to this port? (Choose two.)

- A. DHCP snooping
- B. dynamic ARP inspection
- C. MAC limiting

D. 802.1X

Answer: AB

- 4. Which statement is correct about IS-IS link state PDUs?
- A. They are used to maintain link-state database synchronization.
- B. They are used to establish adjacencies.
- C. They are used to build the link-state database.
- D. They are used to determine whether the neighbors are Level 1 or Level 2.

Answer: C

- 5. Which Junos feature allows you to combine multiple interfaces into a single bundle?
- A. VRRP
- B. Virtual Chassis
- C. LAG
- D. NSB

Answer: C