

QUESTION & ANSWER

Exam Good provides update free of charge in one year!



Exam: RCDD-002

Title : BICSI Registered

Communications

Distribution Designer -

RCDD

Version: DEMO

1.A video camera has a coaxial cable output. The video signal is to be distributed to devices that have balanced twisted pair inputs.

The transition between these two different transmission media can be accomplished by using a:

- A. Balun
- B. Converter
- C. Modulator
- D. Cross connect
- E. Transceiver

Answer: A

- 2. Which is an advantage of stranded conductors over solid conductors?
- A. Less costly
- B. Simpler terminations
- C. Better high frequency performance
- D. More flexible

Answer: D

3. You must place a cable between 2 equipment locations with separate grounds having a potential difference between them of 2.1 V rms.

Which one of the following cables should NOT be used?

- A. Multimode
- B. Singlemode
- C. UTP
- D. STP

Answer: D

- 4. You must place CAT6 cable above a factory floor with automated welding machines and hammer forges.
- Of the following, what type of shielding would be most effective?
- A. Multi-layer braid
- B. Foil and braid
- C. Solid metallic conduit
- D. Flex metallic conduit
- E. Sch. 40 PVC conduit

Answer: C

5. Two sinusoidal signals have the same amplitude (A) and the same frequency (f). They differ in phase by 180 degrees.

If these two signals are added together, the result is a sinusoidal signal having an amplitude of:

- A. Zero
- B. 0.707A and a frequency of f
- C. A and a frequency of 2f
- D. 2A and a frequency of f
- E. 2A and a frequency of 2f

T1 C		4 1 1		1.7	
The safer,	easier way	/ to help v	vou nass	anv H	exams
iiio oaioi ,	oacici maj	to morp	, oa pacc	carry r r	0/(01110.

Answer: A